

For Applications WITH HIGH HUMIDITY

arauco
Moisture Resistant **TRUPAN**

www.arauco-na.com

SPECIFICATION SHEET

An interior, moisture resistant MDF panel that is ideally suited for applications with high humidity and incidental moisture content.

TRUPAN MOISTURE RESISTANT MDF

		Bennettsville, SC		Malvern, AR		
Thickness Range	(in./mm)	3/8 - 13/16	7/8 - 1 1/8	3/8 - 15mm	5/8 - 13/16	7/8 - 1-1/2
Average MOR	(psi)	4,000	4,000	3,000	3,000	2,500
Average MOE	(psi)	500,000	500,000	300,000	300,000	300,000
Average Internal Bond	(psi)	140	120	140	130	110
Face Screw Hold	(lb)	300	275	300	275	275
Edge Screw Hold	(lb)	250	225	N/A	225	225
Thickness Tolerance	(in.)	+/- .005	+/- .005	+/- .005	+/- .005	+/- .005
Length and Width	(in.)	+/- 1/16	+/- 1/16	+/- 1/16	+/- 1/16	+/- 1/16
Squareness	(in.)	+/- 1/8	+/- 1/8	+/- 1/8	+/- 1/8	+/- 1/8

* 24 hour soak - average % (Meets or exceeds ANSI grade MR10).

- The above physical properties are based on target averages of individual production lots. Sampling for conformance to the above specifications must be done in accordance with the procedures described in the American National Standard for MDF. (ANSI A208.2 - 2016 section 6.2 Sampling for Acceptance)
- EPA TSCA Title VI certified - TPC 1.
- Complies with formaldehyde emission requirements in MDF for CAN/CSA-0260-16, CPA-ECC-2011, ANSI 208.2-2016, and CCR 93120 (CARB Composite Wood ATCM Phase II).
- All panels are approved for interior, non-structural application.
- Contains Recycled/Recovered wood content.

Storage and Handling

TRUPAN MDF products should never be stored or used outdoors. The indoor storage area should be clean, dry, well ventilated, and free of dust, dirt or particles that could contaminate the MDF. Store flat on stickers on a level, hard, dry surface. Constant relative humidity and temperature should be maintained. Before use, allow to stabilize to the same conditions as are expected after the panel is installed. Condition 48 to 72 hours prior to lamination. For more information, see Composite Panels Association Technical Bulletin: Storage and Handling of Particleboard and MDF.

California Proposition 65 Requirement:

Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection.

renewables
for a
better life

arauco



proudly supplied by

RUGBY
Architectural Building Products

1-855-650-3265 | www.rugbyabp.com