Titebond® PROvantage Heavy Duty Construction Adhesive

Part No.	Size	Units/ Case	Ctn. Lbs.	Pallet Qty.
5251	10 oz. Cartridge	12	12	108
5252	28 oz Cartridge	12	31	44



Titebond® PROvantage Drywall Adhesive


5342



Titebond® PROvantage Subfloor Construction Adhesive

481	10 oz. Cartridge	12	12	108
	28 oz. Cartridge	12	31	4

Titebond® PROvantage Landscape Adhesive



Titebond® Solvent Based FRP Adhesive

3227	5 Gallon Metal Pail	1	56	36



HAST GRAB

0.0.000

Titeband

ANCED POLYM

Titebond® GREENchoice™ Fast Grab FRP Adhesive

4056	1 Gallon Plastic Pail	2	25	75	Titeb
4054	4 Gallon Plastic Pail	1	49	36	GREEN Choice " ADHESIVES

Titebond[®] GREENchoice[™] Advanced Polymer Panel Adhesive





Titebond°

Titebond°

Titebond[®] GREENchoice[™] Acoustical Ceiling Tile Adhesive

2706	1 Gallon Plastic Pail	2	26	75	
2704	4 Gallon Plastic Pail	1	52	36	GREENchoic



proudly supplied by









Franklin International



Titebond® Heavy Duty Construction Adhesive

Exceeds the APA's AFG-01, ASTM D3498 and ASTM C557 specifications. This versatile, waterproof formula handles practically every job in construction, remodeling or repair. It is designed for a wide range of building materials including wet, frozen and treated lumber, metal, brick, concrete, mirrors, ceramics and most large panel-type substrates. Reduces the amount of nailing and helps eliminate squeaky floors.

Part No.	Size	Units/ Case	Ctn. Lbs.	Pallet Qty.	
5261	10 oz. Cartridge	12	11	108	CONSTRUCTION
5262	28 oz. Cartridge	12	27	44	ADHESIVE

Titebond® Interior/Exterior Construction Adhesive

Specifically designed for use on most common building materials including foams, plastics and wood. Provides excellent water-resistance and works extremely well in colder temperatures. It also offers a 30-minute working time to allow precise placement of materials. It exceeds the performance requirements of ASTM C557.

3451	10 oz. Cartridge	12	12	108		CONSTRUCTION
3452	28 oz. Cartridge	12	32	44		ADHESIVE M


Titebond® Panel & Foamboard Construction Adhesive

Designed for bonding foamboard insulation and polystyrene to most porous building materials. It is also ideal for use on paneling, plastics, tub surrounds, wood, fiberglass, drywall, ceramic tile, metal and more. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.



Titebond[®] All Weather Subfloor Adhesive

An ideal choice for subfloor installations. It is designed for particleboard, OSB, engineered lumber and wet, frozen and treated lumber. It offers a strong initial tack, provides superior strength and remains permanently flexible. Excellent durability - will not become brittle. It reduces the amount of nailing and helps eliminate squeaky floors. Offers excellent cold weather extrudability down to 0°F. It exceeds the performance requirements of AFG-01, ASTM D3498 and ASTM C557 specs.



Titebond® Professional Drywall Adhesive

Designed to apply drywall to wood, hardboard, gypsum wallboard, cold-rolled steel and aluminum. Its strong initial tack allows the panels to be positioned guickly without slipping. Fills irregularities and gaps in substrates, providing a strong bond and a more solid backup surface. It is unaffected by moisture and resists aging. It will not become hard or brittle with age. It exceeds the performance requirements of the ASTM C557 specification.



Titebond® Landscape Retaining Wall Adhesive

A professional-strength adhesive for designed for use on retaining and landscape decorative wall systems. Formulated for use with concrete, wood, brick, masonry, pavers and most other common landscaping materials. Works well on dry, damp and cold surfaces and is strong enough to resist water and frost.

3131 10 oz. Cartridge	12	11	108	S RETAINING WALL
3132 29 oz. Cartridge	12	28	44	adhesive

PROFESSIONAL CONSTRUCTION ADHESIVES Titebond.com • 1.800.347.4583

Titebond[®] GREENchoice[™] Heavy Duty Construction Adhesive

Offers superior interior and exterior strength. Its all-purpose versatility is ideal for all common building materials. It provides a strong grab, fills gaps and irregularities and will remain permanently flexible. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

art No.	Size	Units/ Case	Ctn. Lbs.	Pallet Qty.
7471	10 oz. Cartridge	12	13	108
7472	28 oz. Cartridge	12	33	44
7479	3.5 Gallon Pail	1	44	36

Titebond[®] GREENchoice™ Projects & Repair Construction Adhesive

An interior adhesive designed for general repair and installation projects. The versatile formula has a long working time for precise placement. It exceeds the performance requirements of the ASTM C557 specification.

5311A	10 oz. Cartridge	12	13

Titebond[®] GREENchoice[™] Weatherproof Subfloor Adhesive

A professional-strength formula designed for subfloor installations and plywood use. It provides a permanent bond that remains flexible, reduces nailing and helps eliminate squeaky floors. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

4122	28 oz. Cartridge	12	31

Titebond[®] GREENchoice[™] Professional Drywall Adhesive

Specifically designed for installing drywall and paneling to most common building materials. It offers excellent adhesion, reduces nail pops and provides a "no sag" installation. It exceeds the performance requirements of the ASTM C557 specification. Tested in accordance with E72 for racking and shearing.

7272 28 oz. Cartridge	12	35
-----------------------	----	----

Titebond[®] GREENchoice[™] Professional Cove Base Adhesive

Designed for the quick and easy installation of rubber and vinyl cove bases. Its fast, strong grab holds materials firmly in place and eliminates sagging. It offers excellent adhesion to drywall, plaster, paint, wallpaper, paneling and ceramic tile.

3401	10 oz. Cartridge	12	13	108	COVE BASE	
3402	29 oz. Cartridge	12	35	44	ADHESIVE	
3405	Quart Can	6	20	112	Colonia Constant	
3404	4 Gallon Pail	1	49	36		

Titebond® Fast Set Polyurethane Construction Adhesive

Titebond Fast Set Polyurethane Construction Adhesive is a one-component, advanced adhesive technology designed to build strength faster than other comparable products. It can be used for interior and exterior construction projects, and is the highest performing product of its kind, offering unmatched strength and durability even when bonding non-porous materials. It offers a fast set-up time as well as a smooth bead for effortless extrusion - even in near-freezing temperatures. It is ideal for virtually all building materials, including wet, frozen, engineered and treated lumber, metal, plastic, foam, mirror, concrete and brick.

4221	10 oz. Cartridge	12	15.13
4222	28 oz. Cartridge	12	41.13

PROFESSIONAL CONSTRUCTION ADHESIVES Titebond.com • 1.800.347.4583







